

# MATERIAL SAFETY DATA SHEET

(Prepared According to 29 CFR 1910, 1200) Date Prepared 3/08

## SECTION 1 - PRODUCT IDENTIFICATION

Distributor Name TRUCKMOUNTS & Cleaning Solutions PHONE: (770) 729-7117

Address 5926 Goshen Springs Rd, Norcross GA 30071

Trade Name **MAXX P.O.G. (Paint, Oil & Grease Remover)**

Product Type SOLVENT

Chemical Family - HYDROCARBON MIXTURE

Formula

HAZARD RATING (NFPA704) HEALTH:2 FIRE:1 REACTIVITY:0 SPECIAL:

## SECTION 2 - HAZARDOUS INGREDIENTS

Chemical Name/Common Name	CAS No.	Percent (opt.)	TLV (source)	Sub. to Sec. 313 SARA
d-LIMONENE	5989-27-5			
2-BUTOXYETHANOL	111-76-2		50ppm	
DICHLOROMETHANE	75-09-2	<25	125ppm-STEL(15 min) 25ppm -8hr TWA	YES

## SECTION 3 - PHYSICAL DATA

Boiling Point (F)195F Specific Gravity (H2O=1.05) 0.95 pH- N/A  
Vapor Pressure (mmHg) Vapor Density (Air=1)2.5  
Solubility in Water ( )Complete ( )Insoluble (X)Emulsifiable  
Evaporation Rate (vsH2O) (X)Faster  
Appearance and Odor- PALE YELLOW LIQUID; CITRUS ODOR

## SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point (T.C.C.) (X)None to Boiling Flammable Limits N.A.  
Extinguishing Media - **WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE, FOAM**  
Special Fire Fighting Procedures - **FIREFIGHTERS SHOULD WEAR A SELF CONTAINED BREATHING APPARATUS WITH FULL PROTECTIVE EQUIPMENT. Unusual Fire and Explosion Hazards - AVOID OPEN FLAMES; DECOMPOSITION OF CHLORINE-CONTAINING INGREDIENTS HCL**

## SECTION 5 - REACTIVE DATA

Stability Incompatibility AMINES, ALUMINUM  
Hazardous Decomposition ProductsCARBON MONOXIDE, HCL

## SECTION 6 - HEALTH HAZARDS

Threshold Limit Value - Product (X)None Established ( )Not Applicable (see section 2 for ingredient TLV)  
SourceCarcinogen Suspect Carcinogen Ingredients - (X)ARC GROUP 2B  
Primary Routes of Exposure ( )Eye (X)Skin ( )Oral (X)Inhalation ( )Other  
Signs and Symptoms of Overexposure (Acute) - **PROLONGED EXPOSURE TO VAPOR CONCENTRATIONS OVER 1000 ppm MAY CAUSE DIZZINESS, DRUNKENESS,. PROGRESSIVELY HIGHER CONCENTRATIONS MAY CAUSE UNCONCIOUSNESS AND DEATH. REPEATED CONTACT OF CONCENTRATED PRODUCT WITH SKIN AND/OR EYES MAY CAUSE IRRITATION AND REDDENING. INGESTION MAY CAUSE NAUSEA, VOMITING, DIARRHEA, AND MUCOUSAL IRRITATION.**  
Signs and Symptoms of Overexposure (chronic) - SKIN CONTACT:  
Medical Conditions Aggravated by Overexposure - (X)Pre-existing skin disorder (X)Respiratory deficiency

## SECTION 7 - EMERGENCY FIRST AID PROCEDURES

Eyes - **FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES AND CALL A PHYSICIAN.**  
Skin - **WASH AFFECTED AREAS WITH LARGE AMOUNTS OF SOAP AND WATER. IF IRRITATION PERSISTS, CALL A PHYSICIAN.**  
Ingestion - **DO NOT INDUCE VOMITING. DILUTE BY DRINKING WATER. CALL A PHYSICIAN IMMEDIATELY.**  
Inhalation - **REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED ARTIFICIAL RESPIRATION SHOULD BE STARTED. OXYGEN MAY BE ADMINISTERED IF AVAILABLE. Call a physician. Never give anything by mouth to an unconscious person.**

## SECTION 8 - SPECIAL PROTECTION INFORMATION

Respiratory Protection -ORGANIC VAPOR RESPIRATOR (NIOSH approved)  
Ventilation Requirements ( ) Local exhaust (X)Mechanical ( ) Other  
Protective Gloves- Rubber Eye Protection - SAFETY GLASSES OR GOGGLES  
Other Protective Clothing - **WORK CLOTHING COVERING ARMS & LEGS. APRON & FACE SHIELD IF SPLASHING IS EXPECTED.**

## SECTION 9 - SPILL OR LEAK PROCEDURES

Steps to be Taken if Released or Spilled - **Stop spill at source. Prevent run off. Mop, shovel, pump, and/or absorb with inert material and place in sound containers. Rinse remaining residue with excess water.**  
Waste Disposal Methods - **Dispose of in an approved waste facility according to Federal, State and local regulations.**

## SECTION 10 - STORAGE AND HANDLING INFORMATION

Precautions should be taken in Handling and Storage. No special requirements if product is handled according to good manufacturing practices.  
AVOID OPEN FLAMES, WELDING. D.O.T. - Combustible, NA 1256, UN1256, PG III (containers of 119 gal. or less not regulated by ground)

